



Product Data Sheet

EPOXY TILE EPOXY JOINT FILLER

ABOUT THE PRODUCT

GEPOXY is a three-component system, moisture insensitive epoxy for tile joints. This product supports the joint edges and reduces spalling of the edges caused by wheel traffic. GEPOXY is a chemical resistant and waterproof grout for heavy duty applications. It is recommended for areas where hygiene is utmost important.

BENEFITS OF THE PRODUCT:

- Stain Free
- Colour-Fast
- Easy to Install and Clean Water
- Cleanable Non-Cracking or Powdering
- Anti-Bacteria and Anti-Fungal
- Chemical & Temperature Resistant
- Available in Range of Colours

APPLICATIONS:

Tile Joints.

TECHNICAL SPECIFICATIONS:

Properties	Values
Туре	Three Components (Solid Part & Liquid Part)
Mix Gravity	1.80 Approximate
Pot Lift @ 30 Deg	30 Mins
Tack free time @ 30 Deg	12 Hour
Compressive Strength @ 72 Hr.	210 Kg/cm ²
Tensile Strength @ 7 Days	46 Kg/cm ²

Packaging:

Standard pack size of 1Kg.





Storage & Handling:

GEPOXY is to be stored in cool & dry place.

Safety:

Wear personal protective equipment (PPE). Avoid contact with the eyes and skin. In case of direct contact and irritation, it should be washed off immediately with soap and warm water. It is Non – toxic and non-hazardous but take precaution while handling.



The information given in this data sheet is based on both current development and many years of field experience. While every effort is made to ensure that the information is reliable, we cannot accept responsibility of any work carried out with our products as we have no control over the application procedure adopted at site and site conditions. In view of continuous research and development in our laboratory, we advise customers, in their own interest, to ensure that this data sheet has not been superseded by any other publication. Field services where provided, does not constitute supervisory responsibility. For additional information, Golden Chemical local representative or customer care department may be contacted.